

S P E C I F I C A T I O N

FLEXIBLE VARIABLE RATE VOCODER FOR WIRELESS  
COMMUNICATION SYSTEMS

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention generally relates to speech vocoders, and, more specifically, to flexible variable rate vocoders for wireless communication systems.

2. Background

10 In digital wireless communications systems, a speech vocoder is the device which compresses the digitized the speech signals prior to communication thereof over the wireless channel. Many different compression schemes for speech signals are currently used, including PCM (pulse code modulation), ADPCM (adaptive differential pulse code modulation), and EVRC (Enhanced Variable Rate-Coder). At present, the rate at which a vocoder functions is subject to constraints imposed by the network designer.

15 For example, in current commercial CDMA (code division multiple access) systems, the rate at which the vocoder functions is limited to four possible rates: full rate, half rate, quarter rate, or eighth rate. At full rate, speech is encoded at 170 bits per frame, at half rate, 80 bits per frame, at quarter rate, 40 bits per frame, and at eighth rate, 16 bits per frame. With a 20 ms frame duration, these figures translate into a rate of 8.5 kbit/sec. for full rate, 4 kbit/sec. for half rate, 2 kbit/sec. for quarter rate, and 0.8 kbit/sec. for eighth rate. The rate which is chosen at a time depends on the level of speech activity. For a high level of activity, the full rate is chosen, while for no activity (e.g. silence background), the eighth rate is chosen. For intermediate levels of activity, the half or quarter rates are chosen. Rates greater than 8.5 kbits/sec. or less than 0.8 kbits/sec. are not possible. Since the bit-rate for a particular speech signal varies depending upon the nature of that speech signal, only the average bit-rate is of interest. The average bit-rate is also called average data-rate (ADR).

20 25 30 Recently, a proposal has been made for a selectable mode vocoder (SMV) which is capable of operating in one of three modes. See Test Plan and Requirements

of the Selectable Mode Vocoder, version 8.0, 3GPP2-C13-19991912-007R1, which is hereby fully incorporated by reference herein as though set forth in full. In mode 0, the target ADR of the vocoder is the same as the EVRC (Enhanced Variable Rate Vocoder) rate defined in IS-127 standard. In mode 1, the target ADR is roughly 0.7  
5 that of the EVRC. In mode 2, the target ADR is 0.55-0.6 that of the EVRC, depending on the input signal characteristics, such as speech without background noise or speech with background noises. It is contemplated that the mode of operation of a SMV will be determined by the operator based upon the tradeoff between the network capacity which is available in the system and the desired quality  
10 of service.

A problem with this approach is that, if the network cannot accommodate a demand for services at the desired level of quality, the user will be denied access to the system. Consider, for example, a user who is seeking access to the system in the case in which the network is near saturation. If the desired level of speech activity  
15 requires mode 0, and mode 0 cannot be accommodated by the system, the user will be denied access to the system.

A related problem is loss of flexibility due to the limited number of discrete modes of operation which are available. As detailed above, this loss of flexibility results in users who are denied access to the system. It will also result in lost profit  
20 opportunities as there may be users willing to pay for a higher quality of service than available in the limited number of discrete modes of operation.

#### SUMMARY OF THE INVENTION

In accordance with one aspect of the invention as broadly described herein,  
25 there is provided a flexible variable rate vocoder comprising a rate determination module which selects a target average data rate from a continuous or pseudo-continuous range of possible target rates responsive to at least network parameter and at least one external parameter, and a rate implementation module which sets the rate of outgoing frames so that the actual rate averaged over a predetermined time period  
30 is approximately equal to the target average data rate.

In one embodiment, the rate implementation module sets the rate of outgoing frames by adjusting the relative percentages of outgoing frames which are full rate,

0032024950

half rate, quarter rate, and eighth rate frames such that the average actual rate is approximately equal to the target average rate.

5 In one implementation, the network parameter is available network capacity, and the external parameter is an indicator of the class of service desired or purchased by a user. In one implementation example, the available classes of service comprise premium, standard, and economy. When a demand for network services is received, a determination is made if the network can accommodate the demand at the desired quality. If the network cannot accommodate the demand at the desired quality, the network will reduce the ADR of all non-premium users until the network can  
10 accommodate the demand at the desired quality. If the network can easily accommodate the demand at the desired quality, the network will do so and may then even increase the ADR of all users until the network is close to saturation. In this implementation, the ADR of a premium user starts out at a relatively high rate and remains so despite subsequent changes in demand for network resources. The ADR  
15 of a standard user starts out at a relatively moderate rate, and then changes over time with subsequent changes in demand for network resources. The ADR of an economy user starts out relatively low, and then changes over time with subsequent changes in demand for network resources.

20 In another implementation, the network parameter is available capacity, and the external parameter is an indicator of the subject matter of the information sought to be transmitted. In one implementation example, the available classes of subject matter which can be transmitted comprise voice, data, music, or video. When a demand for network services is received, a determination is made whether the network can accommodate the additional demand at the desired quality. If the  
25 network cannot do so, it will reduce the ADR for selected categories of subject matter, i.e., music, until the network can accommodate the demand at the desired quality. If the network can easily accommodate the desired demand, it will do so, and may even increase the ADR for selected categories of subject matter, e.g., voice and data.

30 In other implementation examples, the external parameter may be the time of day, the weather, etc. Related methods of operation are also provided.

## DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates the discrete quality of service/ capacity tradeoff options which are available in a conventional network.

Figure 2 illustrates the continuous or pseudo-continuous quality of service/capacity tradeoff options which are available in a network configured in accordance with the subject invention.

Figure 3 illustrates an embodiment of a flexible variable rate vocoder in accordance with the subject invention.

Figure 4 illustrates an embodiment of a method of operation in accordance with the subject invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of a flexible variable rate vocoder in accordance with the subject invention is illustrated in Figure 3. As illustrated, in this embodiment, the vocoder includes a rate determination module 8 which selects a target average data rate from a continuous or pseudo-continuous range of possible target rates responsive to at least network parameter 7a and at least one external parameter 7b, and a rate implementation module 18 which sets the rate of outgoing frames so that the actual rate averaged over a predetermined time period is approximately equal to the target average data rate.

For purposes of this disclosure, the term “pseudo-continuous” for a range of modes or parameters means a set of discrete range of modes or parameters that are fine enough to approximate a continuous range of the modes or parameters.

In one implementation, the rate implementation module 18 sets the rate of outgoing frames by adjusting the relative percentages of outgoing frames which are full rate, half rate, quarter rate, and eighth rate frames such that the average actual rate is approximately equal to the target average rate. In this implementation, the rate implementation module 18 comprises switch 9, full rate module 10a, half rate module 10b, quarter rate module 10c, eighth rate module 10d, and multiplexor 11. The multiplexor 11 receives the frames from each of the modules 10a, 10b, 10c, 10d, and serially outputs them on signal line 12.

In other implementations, the rate implementation module 18 is not limited to setting the relative percentages of frames which are full rate, half rate, quarter rate, and eighth rate. For instance, the ITU has standardized a G.729 Annex I where five coding rates are used: 11.2kbit/sec., 8kbit/sec., 6.4kbit/sec., 1.5kbit/sec., and 5 0kbit/sec. Implementations are possible in which the rate implementations module 18 sets the relative percentages of frames which are within these five coding rates. In addition, implementations are possible in which the rate implementation module 18 sets the relative percentages of frames which are within the eight coding rates which are available in the GSM Adaptive Multi-Rate (AMR) coding system.

10 In one implementation, the network parameter is available network capacity, and the external parameter is an indicator of the class of service desired or purchased by a user. In one implementation example, the available classes of service comprise premium, standard, and economy. When a demand for network services is received, a determination is made if the network can accommodate the demand at the desired 15 quality. If the network cannot accommodate the demand at the desired quality, the network will reduce the ADR of all non-premium users until the network can accommodate the demand at the desired quality. If the network can easily accommodate the demand at the desired quality, the network will do so and may then even increase the ADR of all users until the network is close to saturation.

20 In this implementation, the ADR of a premium user starts out at a relatively high rate, and remains so despite subsequent changes in demand for network resources. The ADR of a standard user starts out at a relatively moderate rate, and then changes over time with subsequent changes in demand for network resources. The ADR of an economy user starts out relatively low, and then changes over time 25 with subsequent changes in demand for network resources.

The quality of service/capacity tradeoffs which are available in this implementation can be represented by the curve 6 in Figure 2. The initial quality of service/capacity tradeoff represented by the premium class of service might be 30 represented by numeral 6a; that for the standard class of service, by numeral 6b; and that for the economy class of service, by numeral 6c. As changes in the demand for network services occur, a premium user can move upwards along the curve, but never downwards. The standard user can move upwards or downwards. The economy user

CONFIDENTIAL



An embodiment of a method of operation in accordance with the subject invention is illustrated in Figure 4. The process begins when a demand for network services is initiated. In one implementation, the demand includes a desired level of quality, e.g., premium, standard, or economy. In another implementation, the demand includes a category of subject matter sought to be transmitted, e.g., voice, data, music, image, video, audio, etc., each of which is associated, through one or more lookup tables, with a desired level of quality. The process proceeds to task 14, in which it is queried whether the network can accommodate the demand at the desired level of quality. If not, the process proceeds to step 15, which comprises selectively decreasing the ADRs of existing users (and typically the new user as well) until the demand can be accommodated at the desired quality of service. In one implementation, this step occurs by decreasing the ADRs of non-premium users. In another implementation, this step occurs by decreasing the ADRs of selected categories of subject matter, e.g., music and data. Turning back to task 14, if the demand can be accommodated at the desired level of quality, task 16 is performed. Task 16 comprises accommodating the demand at the desired level of quality. Optional step 17 is then performed which comprises selectively increasing the ADRs of existing users (and typically the new user as well) until the network loading is within a predetermined amount, e.g., 10%, from saturation. In one implementation, this step occurs by increasing the ADRs of all users. In another implementation, it occurs by increasing the ADRs of selected classes of users, e.g., premium and standard users. In yet another implementation, it occurs by increasing the ADRs of selected categories of subject matter, e.g., voice and data.

The vocoder of the subject invention may be included within a transceiver, transmitter, or receiver which in turn may be included in a wireless device, including a mobile wireless device such as a handset, or an immobile wireless device, such as a television set-top box.

While embodiments, implementations, and implementation examples have been shown and described, it should be appreciated that there are many more embodiments, implementations, and implementation examples that are within the scope of the subject invention. Accordingly, the subject invention is not to be restricted, except in light of the appended claims and their equivalents.